



TP 130·N Line Interactive UPS

1100 - 3000 VA single-phase

Power factor 0,9



- + PURE SINE WAVE OUTPUT
- + HIGH RELIABILITY MICROPROCESSOR CONTROL
- + OUTPUT POWER FACTOR 0,9
- + 2-IN-1 RACK AND TOWER FORM FACTOR
- + HOT-SWAPPABLE BATTERY PACK
- + MULTIPLE COMMUNICATION PORTS
- + EMERGENCY POWER OFF (EPO)
- + PROGRAMMABLE POWER MANAGEMENT
- + COMPACT LONG AUTONOMY VERSION



MODEL	TP130N-1100	TP130N-1100-KS*	TP130N-1500	TP130N-2000	TP130N-2000-KS*	TP130N-3000	TP130N-3000-KS*
Power rating VA/W	1100VA / 990W		1500VA / 1350W	2000VA / 1800W		3000VA / 2700W	
INPUT							
Rated Voltage	208/220/230/240 Vac or 110/127 Vac**						
Voltage range	162-290 Vac or 81-145 Vac**						
Frequency Range	50/60 Hz (auto sensing)						
OUTPUT							
Rated Voltage (AC Mode)	208/220/230/240 Vac or 110/127 Vac**						
Voltage Regulation (Batt. Mode)	± 1,5%						
Rated Frequency (Batt. Mode)	50/60 Hz ± 1 Hz						
Power Factor	0,9						
Efficiency	> 97% Eco mode						
Crest Ratio	3:1						
Waveform (Batt. Mode)	Pure Sine Wave						
Transfer Time (Typical)	Typical 2-6 ms, 10 ms max						
BATTERY							
Type	12 V / 9 AH	N/A	12 V / 7 AH	12 V / 9 AH	N/A	12 V / 9 AH	12 V / 9 AH
Numbers of batteries	2	-	4	4	-	6	-
Backup Time (at 50% rated load)	10 minutes	-	12 minutes 30 sec	12 minutes	-	12 minutes	-
Charging Voltage	27,4 Vdc ± 1%		54,8 Vdc ± 1%			82,1 Vdc ± 1%	
Typical recharging time	4h recover to 90% capacity; for KS-long backup version as external batteries capacity						
Charging Current (max)	1,5 Adc	8 Adc	1,5 Adc	1,5 Adc	8 Adc	1,5 Adc	8 Adc
INDICATORS							
LCD Display	AC Mode, Battery Mode, Load Level, Battery Level, Input Voltage, Output Voltage, Overload, Fault and Low Battery						
PROTECTION							
Full Protection	Overload, discharge, and overcharge protection						
ALARM							
Battery Mode	Sounding every 10 seconds						
Low Battery	Sounding every second						
Overload	Sounding twice every 0,5 second						
Fault	Continuously sounding						
PHYSICAL							
Output Receptacles	NEMA**	4			6		
	IEC (standard)	8			7		
Dimension, DXWXH (mm)	410x438x88		510x438x88		410x438x88	610x438x88	230 V: 410x438x88 110 V: 510x438x88
Net Weight (Kg)	13,4	9	19,5	21,5	10,8	29,3	230 V: 11,9 110 V: 13,9
ENVIRONMENT							
Operating Humidity	0-90% RH AT 0- 40°C (non-condensing)						
Noise Level	Less than 40 dB at 1m						
MANAGEMENT							
Standard Communication Interface	USB/RS232 with monitoring Software support Windows 2000/2003/XP/Vista/2008, Windows 7 and later versions, Linux, Unix and Mac.						
Optional Cards	Relay and AS400, SNMP for Ethernet in intellislot.						

* KS version are provided with battery extra charger

**Model available on request

Note: product specifications are subject to change without further information


www.gtec-power.eu


G-Tec Europe srl
 Strada Marosticana, 81/13
 36031 Povolara (VI), Italia
 Tel. +39 0444.361321 - Fax +39 0444.365191
 info@gtec-power.eu

G-Tec France
 Quai du Commerce
 69009 LYON, France
 Tel.: +33 (0) 4 82 81 01 99
 france@gtec-power.eu